



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE

IEC 技术参数		IEC61076-2-101
IEC Technical Data		
工作温度 Operating temperatur [°C]		-25~+80
防护等级 IP Class (IN Locked condition)		IP67
额定电压 Rated Voltage [V]		30
额定电流 Rated Current [A]		2
导线截面积 Conductor cross section		0.25
硬质/柔性导线 Solid/ flexible [mm²]		
接线范围 Wire Range		24
单/多芯线 Solid/Stranded [AWG]		
材料 Material		
绝缘材料 Insulation Material		PA 66
阻燃等级 Imflammability		UL94V-0
导体材料 Contactor Material		铜合金 Copper alloy
导体镀层 Contactive Coating		镀金 Gold Plated
螺母/螺丝 Connector Nut/Screw		Brass With Nickel Plated 铜镀镍
符合RoHS环保要求		

Contacts Pin 数	8Pin
A-Coding	
Rated Current 额定电流	2A
Rated Voltage 额定电压	30V
Wire Range 线范围	24AWG
PART NO.品名: (1M)	M12-A08P-RA0-M02-BCC-100M
PART NO.品名: (2M)	M12-A08P-RA0-M02-BCC-200M
PART NO.品名: (3M)	M12-A08P-RA0-M02-BCC-300M
PART NO.品名: (5M)	M12-A08P-RA0-M02-BCC-500M
Customized.定制化

E	TPU	Molded With Black TPU	G	8	
D	Housing	A-Coding Male 8PIN,Black PA66	pcs	1	
C	Terminal	Male Terminal ,Brass With Gold Plated	pcs	8	
B	Screw	Screw M12 X1.0,Brass With Nickel Plated	pcs	1	
A	Cable	UL TYPE 24AWG X8C Black PVC Jacket	mm	L	
编号 No.	料号 Materials.No	品名 Name	材料规格 Description	单位 Unit	用量 Qty

		慈溪市万捷电子有限公司				PART NO.:	
		CIXI WANJIE ELECTRONIC CO., LTD				M12-A08P-RA0-M02-BCC-XXXX	
NO SPECIFIED TOLERANCE		Cus' P/N:		Order No.:		Drawing No.:	
LINEAR	0.5-6	±0.1	DES.	JUN	DATE	UNITS	mm
	6-30	±0.2	CHK.		DATE	SIZE	A4
	>30	±2%	APP.		DATE	SCALE	X:X
ANGLES	±1°						文件等级: 外部公开